



Name:		Date:			Event:	
City: S	state:	Track:	:			
Track ☐ Indoor ☐ Tight ☐ Smooth ☐	Hard Packed ☐ Blue Groove	■Wet	□ Low Bite	☐ High Bite		
	Loose/Loamy Dry	☐ Dus	ty 🔲 Med Bite	Other _		
Front Suspension	Differentials		Acker	_	Bump Steer	
Toe:	Front: Standard Smart		Lon		Up Down	
Ride Height:	Spring Wire Dia:		Sho	on O	ор Боші	3 2
Camber:	Qty of Springs:			3)		1 —————————————————————————————————————
Caster:	Ramp Plate:		& •			
Wheel Hex:	Grease:					
Sway Bar:	Diff Fluid:					3 08
Piston/Oil:						side 2
Spring:	Center: Standard Sma	art	/ [11	
Limiter/Droop:	Spring Wire Dia:					
Overall Shock Length:	Qty of Springs:				7-A [
Steering Ackerman:	Ramp Plate:				00	
Bump Steer:	Grease:			H		
Camber Link:	Diff Fluid:					
Shock Location:			~	3		
Receiver Battery Type:			Notes:			
Rear Suspension						
Roll Center: HRC LRC						
Toe:			Wing Setu	2		
Anti-Squat:						
Ride Height:			Wing Type: Wing Space			
Camber:			Wicker Bill:			
Rear Hub Spacing:						
Wheel Hex:					3- 2-	
Sway Bar:				DÇBA	1-	
Piston/Oil:						54
Spring:			<i>a</i>			$\frac{3}{2}$
Limiter/Droop:			//	0000	┌ Outside	
Overall Shock Length:					Inside	
Camber Link:						
Shock Location:					191	
Rear Diff Fluid:						
				<u> </u>		
Electronics			Natas:			
Radio: Ser	vo Expo:	[Notes:			
Servo: Mo	tor:					
ESC: Pini	on:					
Initial Brake: Spu	ır:		·			
Drag Brake: Bati	tery:	Tires	Туре		Compound	Insert
Throttle Profile:			·			
Timing Advance:			·			
Throttle/Brake Expo:						
Throttle/Brake EAPA:		Notes	:			_
THOUGH BIANCE IT AL						